Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-263-2801

| Cross | Sectional | Shape: |
|-------|-----------|--------|
| 01033 | ocononiai | onape. |

Mesh and composition

Hole Diameter:

0.240 inches

Overall Length:

3.000 inches

Overall Width:

2.250 inches

Minor Width:

0.125 inches

Inside Corner Radius:

0.120 inches

Outside Corner Radius:

0.120 inches

Aperture Width:

2.000 inches

Aperture Length:

2.750 inches

Center To Center Distance Between Bolt Holes Along Width:

1.870 inches

Center To Center Distance Between Bolt Holes Along Length:

2.620 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.190 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.190 inches

Cross-sectional Height:

0.125 inches

Minor Height:

0.125 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Around rf shielding gasket aperture

Special Features:

4 0.125 in. Diameter x 0.090 in. H compression stops, 1 centrally located on each side

Material:

Rubber butadiene-styrene class sbr environmental seal

Material Specification:

Mil-r-6130, type ii, grade a military specification single material response environmental seal

Style Designator:

Non-circular

NSN 5999-01-263-2801

Electronic Shielding Gasket - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130 spec.

