NSN 5999-01-264-8992



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-264-8992 **Body Style:** Rectangular **Body Length:** 0.510 inches **Body Width:** 0.300 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 0.300 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.310 inches and 0.350 inches **Operating Tempurature Range:** +0.0/+125.0 degrees celsius **Inclosure Type: Encased Mounting Facility Quantity: Voltage Rating:** 25.000 volts Input Impedance Rating: 50.000 ohms **Body Depth:**

0.225 inches

Mounting Facility:

Pin

Attenuation In Decibels:

0.250

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

45.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

9.000 nanoseconds single section all segments

Pulse Rise Time Rating:

11.6 nanoseconds

Terminal Type And Quantity:

8 pin

NSN 5999-01-264-8992

Delay Line - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100