NSN 5999-01-265-0349

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-265-0349

Body Style:
Rectangular
Body Length:
0.870 inches
Body Width:
0.250 inches
Individual Section Quantity:
1
Longest Vertical Distance Between Mounting Centers:
Between 0.320 inches and 0.327 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Inclosure Type:
Encased
Mounting Facility Quantity:
16
Material And Location:
Copper terminal
Input Impedance Rating:
100.000 ohms
Output Impedance Rating:
100.000 ohms
Body Depth:
Between 0.270 inches and 0.275 inches
Mounting Facility:
Pin
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
50.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
5.000 nanoseconds single section all segments
Pulse Rise Time Rating:
10.0 nanoseconds
Terminal Type And Quantity:
16 pin
Special Features:
The same sight to see the same seed 0.400 in the

Two rows, eight terminals per row, spaced 0.100 ins c to c

NSN 5999-01-265-0349

Delay Line - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100