Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-266-4072

| Cross Sectional Shape: |
|------------------------------------------------------------|
| Metal and synthetic rubber |
| Hole Diameter: |
| Between 0.110 inches and 0.130 inches |
| Overall Length: |
| 0.500 inches |
| Overall Width: |
| 0.500 inches |
| Aperture Diameter: |
| Between 0.178 inches and 0.198 inches |
| Outside Corner Inverted Radius: |
| Between 0.110 inches and 0.130 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| 0.340 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| 0.340 inches |
| Outside Edge To Bolt Hole Center Distance Along Width: |
| 0.080 inches |
| Outside Edge To Bolt Hole Center Distance Along Length: |
| 0.080 inches |
| Cross-sectional Thickness: |
| Between 0.016 inches and 0.024 inches |
| Bolt Hole Quantity: |
| 4 |
| Environmental Protection Material Location: |
| Throughout rf shielding gasket |
| Material: |
| Rubber silicone class q environmental seal |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| |
| |