

View Online at <https://aerobasegroup.com/nsn/5999-01-266-4079>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.110 inches and 0.130 inches

Overall Length:

Between 1.258 inches and 1.274 inches

Overall Width:

Between 1.258 inches and 1.274 inches

Aperture Diameter:

Between 1.062 inches and 1.078 inches

Outside Corner Radius:

0.120 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.958 inches and 0.978 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.958 inches and 0.978 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.100 inches and 0.158 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.100 inches and 0.158 inches

Cross-sectional Height:

Between 0.026 inches and 0.036 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Rubber fluorosilicone class fq environmental seal

Material Specification:

Zz-r-765, class 3, grade 30 federal specification single material response environmental seal

Style Designator:

Non-circular

Test Data Document:

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-28840/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A032a0

Mil-std (military Standard):

Mil-c-28840 spec.