

View Online at <https://aerobasegroup.com/nsn/5999-01-266-4079>

**Cross Sectional Shape:**

Emi

**Hole Diameter:**

Between 0.110 inches and 0.130 inches

**Overall Length:**

Between 1.258 inches and 1.274 inches

**Overall Width:**

Between 1.258 inches and 1.274 inches

**Aperture Diameter:**

Between 1.062 inches and 1.078 inches

**Outside Corner Radius:**

0.120 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 0.958 inches and 0.978 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 0.958 inches and 0.978 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.100 inches and 0.158 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.100 inches and 0.158 inches

**Cross-sectional Height:**

Between 0.026 inches and 0.036 inches

**Bolt Hole Quantity:**

4

**Environmental Protection Material Location:**

Throughout rf shielding gasket

**Material:**

Rubber fluorosilicone class fq environmental seal

**Material Specification:**

Zz-r-765, class 3, grade 30 federal specification single material response environmental seal

**Style Designator:**

Non-circular

**Test Data Document:**

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-28840/24 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A032a0

**Mil-std (military Standard):**

Mil-c-28840 spec.