

NSN 5999-01-267-4021 Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-267-4021 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.850 inches **Body Width:** 0.305 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.330 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 16 **Voltage Rating:** 5.000 volts **Material And Location:** Brass terminal err-100 err-100 **Surface Treatment And Location:** Tinned terminal Input Impedance Rating: Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.225 inches

Mounting Facility:

Pin

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Section Delay Time:

100.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

NSN 5999-01-267-4021

Delay Line - Page 2 of 2



Segment Delay Time:
10.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
16 pin
Special Features:
16 mtg pins, 8 per row spaced 0.100 in. C to c, rows spaced 0.330 in. C to c
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100