NSN 5999-01-267-5816

Delay Line - Page 1 of 2

Body Style: Rectangular Body Length:



View Online at https://aerobasegroup.com/nsn/5999-01-267-5816

| 0.750 inches |
|--|
| Body Width: |
| 0.300 inches |
| Individual Section Quantity: |
| 1 |
| Longest Vertical Distance Between Mounting Centers: |
| Between 0.310 inches and 0.350 inches |
| Inclosure Type: |
| Encased |
| Mounting Facility Quantity: |
| 14 |
| Input Impedance Rating: |
| 50.000 ohms |
| Output Impedance Rating: |
| 50.000 ohms |
| Body Depth: |
| 0.225 inches |
| Mounting Facility: |
| Pin |
| Attenuation In Decibels: |
| 0.500 |
| Signal Delay Method: |
| Lumped constant |
| Delay Time Variation Method: |
| Tapped |
| Section Delay Time: |
| 150.000 nanoseconds single section |
| Segment Quantity Per Section: |
| 10 single section |
| Segment Delay Time: |
| 15.000 nanoseconds single section all segments |
| Pulse Rise Time Rating: |
| 20.0 nanoseconds |
| Terminal Type And Quantity: |
| 14 pin |
| Special Features: |
| Two rows, seven pins per row spaced 0.100 in. C to c |
| Shelf Life: |
| N/a |

NSN 5999-01-267-5816

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100