

NSN 5999-01-267-9754 Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-267-9754 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.450 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Plastic, epoxy case err-100 err-100 **Surface Treatment And Location:** Tin plate, mil-t-10727, type 1 or 2 terminal Input Impedance Rating: Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.300 inches

Mounting Facility:

Pin

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Section Delay Time:

100.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

NSN 5999-01-267-9754

Delay Line - Page 2 of 2



10.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

14 pin

Special Features:

14 pins, 7 per row spaced 0.100 in. C to c, rows spaced 0.300 in. C to c

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100