## NSN 5999-01-273-3510



Electrical Contact - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-273-3510 **Overall Length:** Between 0.795 inches and 0.825 inches Pin Diameter: 0.030 inches **Overall Diameter:** 0.063 inches **Cable Entrance Diameter:** Between 0.016 inches and 0.025 inches **Voltage Rating In Volts:** 125.0 ac and 150.0 dc **Current Rating In Amps:** 3.0 **Mounting Method:** Force fit **Special Features:** Retaining clip has a electroless nickel plate per mil-c-26074, class 1 Material: Copper alloy body and contact **Material Specification:** Qq-c-530 federal specification single material response body and contact and qq-c-533 federal specification single material response body and contact and qq-b-626, composition 11, 1/2 hard federal specification single material response body and contact **Precious Material And Location:** Body and contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Surface Treatment:** Gold body and contact and copper body and contact **Surface Treatment Specification:** Mil-g-45204, type ii, grade b or c, class 2 military specification 1st treatment response body and contact **Style Designator:** Pin crimp contact **Terminal Type And Quantity:** 1 crimp end opposite contact Shelf Life: N/a **Unit Of Measure:** 

No **Fiig:** 

ı ııg.

A222a0

**Demilitarization:** 

## NSN 5999-01-273-3510

Electrical Contact - Page 2 of 2



Mil-std (military Standard):

Mil-g-45204 spec.