NSN 5999-01-273-3510

Electrical Contact - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-273-3510

Overall Length:

Between 0.795 inches and 0.825 inches

Pin Diameter:

0.030 inches

Overall Diameter:

0.063 inches

Cable Entrance Diameter:

Between 0.016 inches and 0.025 inches

Voltage Rating In Volts:

125.0 ac and 150.0 dc

Current Rating In Amps:

3.0

Mounting Method:

Force fit

Special Features:

Retaining clip has a electroless nickel plate per mil-c-26074, class 1

Material:

Copper alloy body and contact

Material Specification:

Qq-c-530 federal specification single material response body and contact and qq-c-533 federal specification single material response body and contact and qq-b-626, composition 11, 1/2 hard federal specification single material response body and contact

and contact and qq-b-626, composition 11, 1/2 hard rederal specification single material resp

Precious Material And Location:

Body and contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Gold body and contact and copper body and contact

Surface Treatment Specification:

Mil-g-45204, type ii, grade b or c, class 2 military specification 1st treatment response body and contact

Style Designator:

Pin crimp contact

Terminal Type And Quantity:

1 crimp end opposite contact

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A222a0

NSN 5999-01-273-3510

Electrical Contact - Page 2 of 2

Mil-std (military Standard):

Mil-g-45204 spec.

