NSN 5999-01-273-6747

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-273-6747 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.500 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type: Encased Mounting Facility Quantity: Voltage Rating:** 5.000 volts **Surface Treatment And Location:** Tin plated terminal **Body Depth:** 0.180 inches **Mounting Facility:** Pin **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 150.000 nanoseconds single section **Segment Quantity Per Section:** 5 single section **Segment Delay Time:** 30.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 4.0 nanoseconds **Terminal Type And Quantity:** 8 pin **Special Features:** Two rows, four pins per row, pins are irregularly spaced

Shelf Life: N/a

NSN 5999-01-273-6747

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100