NSN 5999-01-275-0919



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-275-0919 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 1.750 inches **Body Width:** 0.400 inches **Individual Section Quantity: Longest Horizontal Distance Between Mounting Centers:** 1.500 inches **Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 **Voltage Rating:** 100.000 volts **Material And Location:** Copper terminal err-100 err-100 **Surface Treatment And Location:** Tin plated terminal Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.400 inches **Mounting Facility: Terminal Mounting Provision Arrangement Style:** Four position rectangular **Attenuation In Decibels:** 1.000

Signal Delay Method: Inductance

Delay Time Variation Method:

Tapped

NSN 5999-01-275-0919

Delay Line - Page 2 of 2



200.000 nanoseconds single section

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

50.000 nanoseconds

Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100