NSN 5999-01-277-2122

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-277-2122

| Body Style: |
|---|
| Rectangular |
| Body Length: |
| 0.785 inches |
| Body Width: |
| 0.300 inches |
| Individual Section Quantity: |
| 1 |
| Operating Tempurature Range: |
| -55.0/+85.0 degrees celsius |
| Mounting Facility Quantity: |
| 14 |
| Voltage Rating: |
| 50.000 volts |
| Input Impedance Rating: |
| 50.000 ohms |
| Output Impedance Rating: |
| 50.000 ohms |
| Body Depth: |
| 0.300 inches |
| Mounting Facility: |
| Pin |
| Attenuation In Decibels: |
| 1.000 |
| Signal Delay Method: |
| Inductance |
| Delay Time Variation Method: |
| Tapped |
| Section Delay Time: |
| 20.000 nanoseconds single section |
| Segment Quantity Per Section: |
| 10 single section |
| Segment Delay Time: |
| 2.000 nanoseconds single section all segments |
| Pulse Rise Time Rating: |
| 3.3 nanoseconds |
| Terminal Type And Quantity: |
| 14 pin |
| Special Features: |
| 14 pins, 7 per row spaced 0.100 in. C to c, rows spaced 0.560 in. Min to 0.580 in. Maximum c to c |
| Shelf Life: |

N/a

NSN 5999-01-277-2122

Delay Line - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100