NSN 5999-01-278-3549

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-278-3549

Body Style: Rectangular **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity:** 1 Longest Horizontal Distance Between Mounting Centers: 0.600 inches Longest Vertical Distance Between Mounting Centers: 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 8 Voltage Rating: Between 4.750 volts and 5.250 volts Material And Location: Plastic, mil-m-14, type sdg-f case **Surface Treatment And Location:** Lead terminal **Body Depth:** 0.250 inches **Mounting Facility:** Pin **Mounting Provision Arrangement Style:** Four position rectangular Signal Delay Method: Solid state **Delay Time Variation Method:** Tapped **Section Delay Time:** 500.000 nanoseconds single section Segment Quantity Per Section: 5 single section Segment Delay Time: 100.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 4.0 nanoseconds **Terminal Type And Quantity:**

8 pin

NSN 5999-01-278-3549

Delay Line - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100

