NSN 5999-01-279-4443

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-279-4443 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 1.290 inches **Body Width:** 0.600 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** Between 0.590 inches and 0.620 inches **Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 24 **Voltage Rating:** Not rated **Material And Location:** Iron alloy terminal err-100 err-100 **Surface Treatment And Location:** Tin plate terminal Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.300 inches **Unpackaged Unit Weight:**

10.0 grams **Mounting Facility:** Pin **Attenuation In Decibels:** 1.000 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped**

NSN 5999-01-279-4443

Delay Line - Page 2 of 2



_		-				
•	ectio	nn I	וםנ	21/	lım	ο.
•	CCLIC	JII L	761	av		┖.

1.900 microseconds single section and 2.100 microseconds single section

Segment Quantity Per Section:

6 single section

Segment Delay Time:

1.805 microseconds single section 5th segment err-100 and 1.995 microseconds single section 5th segment err-100

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

2.0 microseconds

Terminal Type And Quantity:

24 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32100