Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-280-1163

Cross Sectional Shape:
Mesh and metal
Hole Diameter:
Between 0.404 inches and 0.413 inches
Overall Length:
Between 19.580 inches and 19.700 inches
Overall Width:
Between 13.100 inches and 13.220 inches
Aperture Width:
Between 10.040 inches and 10.280 inches
Aperture Length:
Between 16.960 inches and 17.200 inches
Center To Center Distance Between Bolt Holes Along Width:
5.960 inches
Center To Center Distance Between Bolt Holes Along Length:
4.600 inches
Outside Edge To Bolt Hole Center Distance Along Width:
Between 0.570 inches and 0.690 inches
Outside Edge To Bolt Hole Center Distance Along Length:
Between 0.570 inches and 0.690 inches
Cross Section Outside Diameter:
Between 0.220 inches and 0.280 inches
Cross-sectional Height:
Between 0.220 inches and 0.280 inches
Bolt Hole Quantity:
12
Environmental Protection Material Location:
Around rf shielding gasket aperture and around rf shielding gasket outer perimeter
Material:
Rubber synthetic environmental seal
Material Specification:
Qq-a-200/9, t4 federal specification 1st material response emi/rfi conductor
Surface Treatment:
Copper emi/rfi conductor and tin emi/rfi conductor
Style Designator:
Non-circular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5999-01-280-1163

Electronic Shielding Gasket - Page 2 of 2



Fiig: A032a0

Mil-std (military Standard):

Mil-r-6130 spec.