Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-280-1424

C	Cross Sectional Shape:
L	inked wire and composition
ŀ	Hole Diameter:
E	Between 0.131 inches and 0.151 inches
C	Overall Length:
E	Between 1.422 inches and 1.452 inches
C	Overall Width:
E	Between 1.422 inches and 1.452 inches
ł	Aperture Diameter:
E	Between 1.198 inches and 1.238 inches
C	Dutside Corner Radius:
E	Between 0.495 inches and 0.566 inches
C	Center To Center Distance Between Bolt Holes Along Width:
E	Between 1.052 inches and 1.072 inches
C	Center To Center Distance Between Bolt Holes Along Length:
E	Between 1.052 inches and 1.072 inches
C	Dutside Edge To Bolt Hole Center Distance Along Width:
E	Between 0.175 inches and 0.200 inches
C	Dutside Edge To Bolt Hole Center Distance Along Length:
E	Between 0.175 inches and 0.200 inches
C	Cross-sectional Height:
E	Between 0.015 inches and 0.025 inches
E	Bolt Hole Quantity:
4	l
E	Environmental Protection Material Location:
٦	Throughout rf shielding gasket
Ν	Material:
F	Rubber silicone class q environmental seal
Ν	Material Specification:
Z	Zz-r-765, class 2b, grade 50 federal specification single material response environmental seal
5	Style Designator:
٢	Non-circular
5	Specification Data:
g	00536-7916258-01 manufacturers specification control
S	Shelf Life:
٢	N/a
ι	Jnit Of Measure:
-	-
0	Demilitarization:
١	No
F	Filg:
A	A032a0