## NSN 5999-01-280-2185

Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-280-2185
Cross Sectional Shape:
Linked wire and composition
Hole Diameter:
Between 0.156 inches and 0.166 inches
Overall Length:
Between 14.525 inches and 14.535 inches
Overall Width:
Between 4.245 inches and 4.255 inches
Inside Corner Radius:
0.250 inches
Aperture Width:
Between 3.245 inches and 3.255 inches
Aperture Length:
Between 13.525 inches and 13.535 inches
Outside Corner Bevel Length Along Width:
Between 0.151 inches and 0.161 inches
Outside Corner Bevel Length Along Length:
Between 0.151 inches and 0.161 inches
Center To Center Distance Between Bolt Holes Along Width:
Between 2.871 inches and 2.881 inches
Center To Center Distance Between Bolt Holes Along Length:
Between 2.323 inches and 2.333 inches
Cross-sectional Height:
Between 0.016 inches and 0.024 inches
Bolt Hole Quantity:
14
Environmental Protection Material Location:
Throughout rf shielding gasket
Material:
Rubber chloroprene class cr environmental seal
Material Specification:
Mil-r-6855, class 2 military specification single material response environmental seal
Style Designator:
Non-circular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A032a0

## NSN 5999-01-280-2185

Electronic Shielding Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-r-6855 spec.