Electronic Shielding Gasket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-280-2185

| Cross Sectional Shape: |
|--|
| Linked wire and composition |
| Hole Diameter: |
| Between 0.156 inches and 0.166 inches |
| Overall Length: |
| Between 14.525 inches and 14.535 inches |
| Overall Width: |
| Between 4.245 inches and 4.255 inches |
| Inside Corner Radius: |
| 0.250 inches |
| Aperture Width: |
| Between 3.245 inches and 3.255 inches |
| Aperture Length: |
| Between 13.525 inches and 13.535 inches |
| Outside Corner Bevel Length Along Width: |
| Between 0.151 inches and 0.161 inches |
| Outside Corner Bevel Length Along Length: |
| Between 0.151 inches and 0.161 inches |
| Center To Center Distance Between Bolt Holes Along Width: |
| Between 2.871 inches and 2.881 inches |
| Center To Center Distance Between Bolt Holes Along Length: |
| Between 2.323 inches and 2.333 inches |
| Cross-sectional Height: |
| Between 0.016 inches and 0.024 inches |
| Bolt Hole Quantity: |
| 14 |
| Environmental Protection Material Location: |
| Throughout rf shielding gasket |
| Material: |
| Rubber chloroprene class cr environmental seal |
| Material Specification: |
| Mil-r-6855, class 2 military specification single material response environmental seal |
| Style Designator: |
| Non-circular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A032a0 |
| |
| |

Electronic Shielding Gasket - Page 2 of 2



Mil-std (military Standard):

Mil-r-6855 spec.