NSN 5999-01-284-2908

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-284-2908 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 1.550 inches **Body Width:** 0.300 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 28 **Voltage Rating:** 12.000 volts **Material And Location:** Plastic, epoxy case err-100 err-100 **Surface Treatment And Location:** Tin plate, mil-t-10727, type 1 or 2 terminal Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.265 inches **Mounting Facility:** Pin **Attenuation In Decibels:** Not rated **Signal Delay Method:** Inductance **Delay Time Variation Method:** Tapped **Section Delay Time:**

48.000 nanoseconds single section

NSN 5999-01-284-2908

Delay Line - Page 2 of 2

Fiig: A32100



Segment Quantity Per Section:
11 single section
Segment Delay Time:
38.000 nanoseconds single section 1st segment err-100
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
Not rated
Terminal Type And Quantity:
28 pin
Special Features:
Two rows, fourteen pins per row, pins spaced 0.100 in. $\mbox{\em C}$ to $\mbox{\em c}$
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli