

View Online at <https://aerobasegroup.com/nsn/5999-01-286-6592>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.115 inches and 0.135 inches

Overall Length:

Between 1.328 inches and 1.358 inches

Temperature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Overall Width:

Between 1.328 inches and 1.358 inches

Aperture Diameter:

Between 1.189 inches and 1.209 inches

Outside Corner Radius:

0.198 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.052 inches and 1.072 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.052 inches and 1.072 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.128 inches and 0.153 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.128 inches and 0.153 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Rubber fluorosilicone class fq environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0