

View Online at <https://aerobasegroup.com/nsn/5999-01-286-6660>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

Between 0.740 inches and 0.780 inches

Body Width:

Between 0.290 inches and 0.320 inches

Individual Section Quantity:

1

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

14

Voltage Rating:

Not rated

Material And Location:

Plastic, epoxy body err-100 err-100

Surface Treatment And Location:

Tin plate, mil-t-10727, type 1 or 2 terminal

Input Impedance Rating:

200.000 ohms

Output Impedance Rating:

200.000 ohms

Frequency Bandwidth:

Not rated

Body Depth:

Between 0.177 inches and 0.197 inches

Mounting Facility:

Terminal

Attenuation In Decibels:

5.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

100.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

10.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

20.0 nanoseconds

Terminal Type And Quantity:

14 pin

Test Data Document:

81349-mil-d-23859 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-d-23859/23 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100