Electronic Shielding Gasket - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5999-01-289-0916

Cr	oss Sectional Shape:
Wi	ire and composition
Ho	ble Diameter:
Be	tween 0.090 inches and 0.110 inches
Ov	verall Length:
Be	tween 0.672 inches and 0.702 inches
Ov	verall Width:
Be	tween 0.672 inches and 0.702 inches
Ap	perture Diameter:
Be	tween 0.417 inches and 0.457 inches
Οι	utside Corner Radius:
0.1	132 inches
Ce	enter To Center Distance Between Bolt Holes Along Width:
Be	tween 0.490 inches and 0.510 inches
Ce	enter To Center Distance Between Bolt Holes Along Length:
Be	tween 0.490 inches and 0.510 inches
Οι	utside Edge To Bolt Hole Center Distance Along Width:
0.0	094 inches
Οι	utside Edge To Bolt Hole Center Distance Along Length:
0.0	094 inches
Cr	oss-sectional Height:
0.0	032 inches
Bo	olt Hole Quantity:
4	
En	vironmental Protection Material Location:
Th	roughout rf shielding gasket
Ма	aterial:
Ru	ubber silicone class q environmental seal
Ма	aterial Specification:
Zz	-r-765, class 2 federal specification single material response environmental seal
St	yle Designator:
No	on-circular
Sh	nelf Life:
N/a	a
Un	nit Of Measure:
De	emilitarization:
No	
Fii	ig:
)32a0