

View Online at <https://aerobasegroup.com/nsn/5999-01-291-8977>

Body Style:

Rectangular

Frequency Rating:

Not rated

Body Length:

0.810 inches

Body Width:

0.510 inches

Individual Section Quantity:

1

Longest Vertical Distance Between Mounting Centers:

Between 0.290 inches and 0.310 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Rating:

4.500 volts

Material And Location:

Plastic, diallyl phthalate, mil-m-14, type mdg case or plastic, epoxy case

Input Impedance Rating:

Not rated

Output Impedance Rating:

Not rated

Frequency Bandwidth:

Not rated

Body Depth:

0.165 inches

Mounting Facility:

Terminal

Attenuation In Decibels:

Not rated

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

248.000 nanoseconds single section and 252.000 nanoseconds single section

Segment Quantity Per Section:

5 single section

Segment Delay Time:

95.000 nanoseconds single section 2nd segment err-100 and 105.000 nanoseconds single section 2nd segment err-100

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 pin

Special Features:

Eight pins available in a fourteen pack package

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100