## NSN 5999-01-292-2022

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-292-2022

Body Style:
Rectangular
Frequency Rating:
Not rated
Body Length:
0.780 inches
Body Width:
0.280 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Mounting Facility Quantity:
14
Voltage Rating:
Between 4.750 volts and 5.250 volts
Input Impedance Rating:
Not rated
Output Impedance Rating:
Not rated
Frequency Bandwidth:
Not rated
Body Depth:
0.250 inches
Mounting Facility:
Pin
Attenuation In Decibels:
Not rated
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
250.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
25.000 nanoseconds single section all segments
Delay Time Variation Per Deg Celsius:
Not rated
Pulse Rise Time Rating:
2.0 nanoseconds

## NSN 5999-01-292-2022

Delay Line - Page 2 of 2



<b>Terminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

14 pin

## **Special Features:**

14 mtg pins, 7 per row spaced 0.100 in. C to c, rows spaced 0.365 in. Maximum c to c

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

## Demilitarization:

Yes - demil/mli

Fiig:

A32100