

View Online at <https://aerobasegroup.com/nsn/5999-01-293-6442>

Body Style:

Rectangular

Adjustment Device Quantity:

1

Adjustment Device Drive Type:

Slotted screw

Body Length:

1.600 inches

Body Width:

0.840 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.100 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2

Voltage Rating:

50.000 volts

Input Impedance Rating:

100.000 ohms

Output Impedance Rating:

100.000 ohms

Body Depth:

Between 0.570 inches and 0.630 inches

Mounting Facility:

Terminal

Mounting Provision Arrangement Style:

2 position in-line

Attenuation In Decibels:

2.000

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Variable

Section Delay Time:

0.000 nanoseconds single section and 11.000 nanoseconds single section

Pulse Rise Time Rating:

2.0 nanoseconds

Terminal Type And Quantity:

2 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32100