## NSN 5999-01-297-3540

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-297-3540 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Voltage Rating:** Between 4.500 volts and 5.500 volts **Material And Location:** Brass terminal err-100 err-100 **Surface Treatment And Location:** Gold, mil-g-45204, type 2, class 2 terminal Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.320 inches **Mounting Facility:** Pin **Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped

**Section Delay Time:** 

500.000 nanoseconds single section

**Delay Time Variation Per Deg Celsius:** 

Not rated

## NSN 5999-01-297-3540

Delay Line - Page 2 of 2



Pulse Rise Time Rating:
5.0 nanoseconds
Terminal Type And Quantity:
8 pin
<b>Precious Material And Location:</b>
Terminal gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A32100