

| | SN 5999-01-297-5910 ectronic Shielding Gasket - Page 1 of 2 | Aerobas |
|-----|--|---------|
| Vie | ew Online at https://aerobasegroup.com/nsn/5999-01-297-5910 | |
| Cro | oss Sectional Shape: | |
| Em | ni hollow | |
| Ho | le Diameter: | |
| Bet | tween 0.098 inches and 0.106 inches | |
| Ove | erall Length: | |
| 19. | .240 inches | |
| Ter | mpurature Rating: | |
| -55 | 5.0 degrees celsius and 125.0 degrees celsius | |
| Ove | erall Width: | |
| 7.4 | 60 inches | |
| | | |

Inside Corner Radius:

0.060 inches

Aperture Width:

5.960 inches

Aperture Length:

17.740 inches

Center To Center Distance Between Bolt Holes Along Width:

2.500 inches

Center To Center Distance Between Bolt Holes Along Length:

2.173 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.464 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.464 inches

Cross Section Inside Diameter:

Between 0.070 inches and 0.090 inches

Cross Section Outside Diameter:

Between 0.190 inches and 0.210 inches

Bolt Hole Quantity:

24

End Application:

1440-01-087-9844 launching station guided missile semitrailer mounted

Material:

Rubber silicone class q environmental seal

Material Specification:

Qq-a-250/11, t6 federal specification single material response stop

Surface Treatment:

Silver emi/rfi conductor

Surface Treatment Specification:

Mil-c-5541, cl 1a or cl 3 military specification single treatment response stop

Style Designator:

Non-circular

NSN 5999-01-297-5910

Electronic Shielding Gasket - Page 2 of 2



| N/a | | | |
|-------------------|--|--|--|
| Unit Of Measure: | | | |
| | | | |
| Demilitarization: | | | |
| No | | | |
| Fiig: | | | |
| A032a0 | | | |

Mil-std (military Standard):

Mil-c-5541 spec.

Shelf Life: