NSN 5999-01-302-3410



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-302-3410 **Body Style:** Rectangular **Body Length:** 0.820 inches **Body Width:** 0.430 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 14 **Material And Location:** Plastic, diallyl phthalate, mil-m-14, type mdg case or plastic, epoxy case **Surface Treatment And Location:** Tin plate case Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms **Body Depth:** 0.280 inches Step Quantity: 8 **Mounting Facility: Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Programmable **Delay Time Per Step:** 10.000 nanoseconds **Section Delay Time:** 70.000 nanoseconds single section **Pulse Rise Time Rating:** 5.0 nanoseconds **Terminal Type And Quantity:** 14 pin

Shelf Life: N/a

NSN 5999-01-302-3410

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100