NSN 5999-01-305-0459

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-305-0459 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Voltage Rating:** Between 4.750 volts and 5.250 volts **Material And Location:** Plastic, epoxy body err-100 err-100 **Surface Treatment And Location:** Tin plate, mil-t-10727, type 1 or 2 terminal Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.260 inches **Mounting Facility: Terminal Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 200.000 nanoseconds single section **Segment Quantity Per Section:**

5 single section

NSN 5999-01-305-0459

Delay Line - Page 2 of 2



Segment De	elay Time:
------------	------------

40.000 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

4.0 nanoseconds

Terminal Type And Quantity:

8 tab solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100