

View Online at <https://aerobasegroup.com/nsn/5999-01-305-5202>

Cross Sectional Shape:

Mesh and metal

Hole Diameter:

Between 0.135 inches and 0.145 inches

Overall Length:

Between 5.869 inches and 5.879 inches

Overall Width:

Between 4.069 inches and 4.079 inches

Aperture Width:

Between 2.695 inches and 2.705 inches

Aperture Length:

Between 4.495 inches and 4.505 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.295 inches and 1.305 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.745 inches and 1.755 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.195 inches and 0.205 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.195 inches and 0.205 inches

Cross Section Outside Diameter:

Between 0.188 inches and 0.313 inches

Cross-sectional Height:

Between 0.088 inches and 0.098 inches

Minor Height:

Between 0.088 inches and 0.098 inches

Bolt Hole Quantity:

10

Environmental Protection Material Location:

Center

Special Features:

Aluminum alloy extrusion 6063-t42 per qq-a-274 with conductive chromate finish per mil-c-5541 located around the rf shielding gasket outer perimeter

Material:

Steel emi/rfi conductor

Material Specification:

Mil-r-6130, type ii, grade a, condition medium military specification single material response environmental seal

Surface Treatment:

Copper emi/rfi conductor and tin emi/rfi conductor

Style Designator:

Non-circular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0

Mil-std (military Standard):

Mil-r-6130 spec.