

View Online at <https://aerobasegroup.com/nsn/5999-01-305-5202>

**Cross Sectional Shape:**

Mesh and metal

**Hole Diameter:**

Between 0.135 inches and 0.145 inches

**Overall Length:**

Between 5.869 inches and 5.879 inches

**Overall Width:**

Between 4.069 inches and 4.079 inches

**Aperture Width:**

Between 2.695 inches and 2.705 inches

**Aperture Length:**

Between 4.495 inches and 4.505 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 1.295 inches and 1.305 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.745 inches and 1.755 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.195 inches and 0.205 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.195 inches and 0.205 inches

**Cross Section Outside Diameter:**

Between 0.188 inches and 0.313 inches

**Cross-sectional Height:**

Between 0.088 inches and 0.098 inches

**Minor Height:**

Between 0.088 inches and 0.098 inches

**Bolt Hole Quantity:**

10

**Environmental Protection Material Location:**

Center

**Special Features:**

Aluminum alloy extrusion 6063-t42 per qq-a-274 with conductive chromate finish per mil-c-5541 located around the rf shielding gasket outer perimeter

**Material:**

Steel emi/rfi conductor

**Material Specification:**

Mil-r-6130, type ii, grade a, condition medium military specification single material response environmental seal

**Surface Treatment:**

Copper emi/rfi conductor and tin emi/rfi conductor

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-6130 spec.