## NSN 5999-01-305-8811

Delay Line - Page 1 of 2

7 tab solder lug



View Online at https://aerobasegroup.com/nsn/5999-01-305-8811

Body Style:
Rectangular
Frequency Rating:
1.000 megahertz
Body Length:
0.800 inches
Body Width:
0.230 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
7
Voltage Rating:
25.000 volts
Input Impedance Rating:
50.000 ohms
Output Impedance Rating:
50.000 ohms
Body Depth:
0.200 inches
Mounting Facility:
Terminal
Attenuation In Decibels:
0.250
Signal Delay Method:
Lumped constant
Delay Time Variation Method:
Tapped
Section Delay Time:
47.500 nanoseconds single section and 52.500 nanoseconds single section
Segment Quantity Per Section:
5 single section
Segment Delay Time:
8.000 nanoseconds single section all segments and 12.000 nanoseconds single section all segments
Pulse Rise Time Rating:
13.0 nanoseconds
Terminal Type And Quantity:

## NSN 5999-01-305-8811

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100