NSN 5999-01-306-2518

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-306-2518 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** Between 4.750 volts and 5.250 volts **Material And Location:** Plastic, epoxy body err-100 err-100 **Surface Treatment And Location:** Tin plated, mil-t-10727, type 2 terminal Input Impedance Rating: Not rated **Output Impedance Rating:** Not rated Frequency Bandwidth: Not rated **Body Depth:** 0.260 inches **Mounting Facility: Terminal Attenuation In Decibels:** Not rated **Signal Delay Method:** Lumped constant **Delay Time Variation Method:** Tapped **Section Delay Time:** 40.000 nanoseconds all sections

Not rated

Delay Time Variation Per Deg Celsius:

NSN 5999-01-306-2518

Delay Line - Page 2 of 2



Ρ	ulse	Rise	Time	Rating:

4.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A32100