

View Online at <https://aerobasegroup.com/nsn/5999-01-306-8873>

Special Features:

Aluminum alloy 6061-t6 per qq-a-250/11; 6.300 in. Lg; 2.820 in. W; 0.550 in. Thk; two 0.290 in. Min diameter to 0.293 in. Maximum diameter unthd through holes countersunk 0.330 in. Diameter x eighty-two degrees, spaced 1.505 in. C to c; ninety-four 0.062 in. Diameter unthd through holes irregularly spaced; twenty-four 0.078 in. Diameter unthd holes irregularly spaced; seventeen 0.116 in. Diameter unthd through holes irregularly spaced; two 0.140 in. Diameter unthd through holes spaced 0.590 in. C to c; four 0.156 in. Diameter unthd through holes irregularly spaced; thirty-nine 0.057 in. Diameter unthd through holes irregularly spaced; twen type 0.093 in. Diameter unthd through holes irregularly spaced; five 0.166 in. Diameter unthd through holes irregularly spaced; one 0.277 in. Diameter unthd through hole; one 0.213 in. Diameter unthd through hole; one 0.128 in. Diameter unthd through hole; two 0.125 in. Diameter unthd through holes spaced 1.125 in. C to c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03600