## NSN 5999-01-310-5751

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-310-5751 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.750 inches **Body Width:** 0.300 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Mounting Facility Quantity:** 14 **Voltage Rating:** 25.000 volts **Material And Location:** Fiberglass, epoxy case err-100 err-100 **Surface Treatment And Location:** Tin plate terminal Input Impedance Rating: 50.000 ohms **Output Impedance Rating:** 50.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.225 inches **Mounting Facility: Terminal Attenuation In Decibels:** 0.500 **Signal Delay Method:** Lumped constant **Delay Time Variation Method: Tapped Section Delay Time:** 10.000 nanoseconds single section **Segment Quantity Per Section:** 10 single section

**Segment Delay Time:** 

1.000 nanoseconds single section all segments

## NSN 5999-01-310-5751

Delay Line - Page 2 of 2



Pu	lse	Rise	Time	Rating	1:

3.0 nanoseconds

**Terminal Type And Quantity:** 

14 pin

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

Yes - demil/mli

Fiig:

A32100