

View Online at <https://aerobasegroup.com/nsn/5999-01-310-9459>

Body Style:

Rectangular

Body Length:

0.750 inches

Body Width:

0.300 inches

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.100 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.310 inches and 0.350 inches

End Application:

1430-01-286-1314guided missile

Mounting Facility Quantity:

14

Voltage Rating:

25.000 volts

Input Impedance Rating:

50.000 ohms

Output Impedance Rating:

50.000 ohms

Body Depth:

0.225 inches

Mounting Facility:

Pin

Attenuation In Decibels:

0.500

Signal Delay Method:

Lumped constant

Delay Time Variation Method:

Tapped

Section Delay Time:

80.000 nanoseconds single section

Segment Quantity Per Section:

10 single section

Segment Delay Time:

8.000 nanoseconds single section all segments

Pulse Rise Time Rating:

10.0 nanoseconds

Terminal Type And Quantity:

14 pin

Special Features:

Fourteen pins, seven per row spaced 0.100 in. C to c, rows spaced 0.310 in. Min to 0.350 in. Maximum c to c

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100