

View Online at <https://aerobasegroup.com/nsn/5999-01-310-9459>

**Body Style:**

Rectangular

**Body Length:**

0.750 inches

**Body Width:**

0.300 inches

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

0.100 inches

**Longest Vertical Distance Between Mounting Centers:**

Between 0.310 inches and 0.350 inches

**End Application:**

1430-01-286-1314guided missile

**Mounting Facility Quantity:**

14

**Voltage Rating:**

25.000 volts

**Input Impedance Rating:**

50.000 ohms

**Output Impedance Rating:**

50.000 ohms

**Body Depth:**

0.225 inches

**Mounting Facility:**

Pin

**Attenuation In Decibels:**

0.500

**Signal Delay Method:**

Lumped constant

**Delay Time Variation Method:**

Tapped

**Section Delay Time:**

80.000 nanoseconds single section

**Segment Quantity Per Section:**

10 single section

**Segment Delay Time:**

8.000 nanoseconds single section all segments

**Pulse Rise Time Rating:**

10.0 nanoseconds

**Terminal Type And Quantity:**

14 pin

**Special Features:**

Fourteen pins, seven per row spaced 0.100 in. C to c, rows spaced 0.310 in. Min to 0.350 in. Maximum c to c

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A32100