## NSN 5999-01-312-8133

Electronic Shielding Gasket - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5999-01-312-8133                            |
|--|
| Cross Sectional Shape:   |
| Emi  |
| Hole Diameter:   |
| Between 0.110 inches and 0.140 inches  |
| Overall Length:  |
| Between 1.173 inches and 1.203 inches  |
| Tempurature Rating:  |
| -0.620 degrees celsius and 250.0 degrees celsius   |
| Overall Width:   |
| Between 1.173 inches and 1.203 inches  |
| Aperture Diameter:   |
| Between 0.969 inches and 0.999 inches  |
| Outside Corner Radius:   |
| 0.125 inches   |
| Center To Center Distance Between Bolt Holes Along Width:                                |
| Between 0.891 inches and 0.921 inches  |
| Center To Center Distance Between Bolt Holes Along Length:                               |
| Between 0.891 inches and 0.921 inches  |
| Outside Edge To Bolt Hole Center Distance Along Width:                                   |
| 0.141 inches   |
| Outside Edge To Bolt Hole Center Distance Along Length:                                  |
| 0.141 inches   |
| Cross-sectional Height:  |
| Between 0.016 inches and 0.024 inches  |
| Bolt Hole Quantity:  |
| 4  |
| Environmental Protection Material Location:  |
| Throughout rf shielding gasket   |
| Material:  |
| Rubber silicone class q environmental seal   |
| Material Specification:  |
| Zz-r-765, cl 2b, gr 50 federal specification single material response environmental seal |
| Style Designator:  |
| Non-circular   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

Fiig:

A032a0