NSN 5999-01-321-4032

Delay Line - Page 1 of 2

Body Style: Rectangular



 \boldsymbol{C} to \boldsymbol{c} on one row, remaining six terminals spaced 0.100 in. \boldsymbol{C} to \boldsymbol{c} on another row

View Online at https://aerobasegroup.com/nsn/5999-01-321-4032

Body Length:
0.800 inches
Body Width:
0.400 inches
Individual Section Quantity:
1
Longest Vertical Distance Between Mounting Centers:
0.300 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Inclosure Type:
Encased
Mounting Facility Quantity:
13
Voltage Rating:
Between 4.750 volts and 5.250 volts
Material And Location:
Plastic, mil-m-14, type sdg-f body
Surface Treatment And Location:
Plastic, epoxy body
Body Depth:
0.260 inches
Mounting Facility:
Pin
Signal Delay Method:
Solid state
Delay Time Variation Method:
Tapped
Section Delay Time:
500.000 nanoseconds single section
Segment Quantity Per Section:
10 single section
Segment Delay Time:
50.000 nanoseconds single section all segments
Pulse Rise Time Rating:
4.0 nanoseconds
Terminal Type And Quantity:
13 pin
Special Features:
Thirteen terminals, seven terminals spaced 0.100 in. C to c

NSN 5999-01-321-4032

Delay Line - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100