## NSN 5999-01-321-4032

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-321-4032

**Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.400 inches **Individual Section Quantity:** 1 Longest Vertical Distance Between Mounting Centers: 0.300 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius **Inclosure Type:** Encased **Mounting Facility Quantity:** 13 Voltage Rating: Between 4.750 volts and 5.250 volts Material And Location: Plastic, mil-m-14, type sdg-f body **Surface Treatment And Location:** Plastic, epoxy body **Body Depth:** 0.260 inches **Mounting Facility:** Pin Signal Delay Method: Solid state **Delay Time Variation Method:** Tapped Section Delay Time: 500.000 nanoseconds single section Segment Quantity Per Section: 10 single section Segment Delay Time: 50.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 4.0 nanoseconds **Terminal Type And Quantity:** 13 pin

**Special Features:** 

Thirteen terminals, seven terminals spaced 0.100 in. C to c on one row, remaining six terminals spaced 0.100 in. C to c on another row

## NSN 5999-01-321-4032

Delay Line - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100

