View Online at https://aerobasegroup.com/nsn/5999-01-323-3804

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.015 inches and 0.035 inches

Overall Length:

Between 1.235 inches and 1.265 inches

Tempurature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Overall Width:

Between 1.235 inches and 1.265 inches

Aperture Diameter:

Between 1.063 inches and 1.083 inches

Outside Corner Radius:

Between 0.362 inches and 0.433 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.959 inches and 0.979 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.959 inches and 0.979 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.256 inches and 0.306 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.256 inches and 0.306 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Rubber silicone class q environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0