NSN 5999-01-324-9611



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-324-9611 **Body Style:** Cylindrical, end post connection **Overall Length:** Between 0.813 inches and 0.999 inches **Body Diameter:** 0.705 inches **Body Length:** Between 0.375 inches and 0.499 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+105.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity: Voltage Rating:** 100.000 volts **Material And Location:** Brass terminal or copper terminal **Surface Treatment And Location:** Tin plate terminal or gold, mil-g-45204, type 2, class 2 terminal Input Impedance Rating: 500.000 ohms **Output Impedance Rating:** 500.000 ohms **Mounting Facility:** Pin **Signal Delay Method:** Lumped constant **Section Delay Time:** 48.000 nanoseconds single section and 52.000 nanoseconds single section **Pulse Rise Time Rating:** 10.0 nanoseconds **Terminal Type And Quantity:** 3 pin **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold

Shelf Life: N/a

NSN 5999-01-324-9611

Delay Line - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100