

View Online at <https://aerobasegroup.com/nsn/5999-01-327-9285>

**Cross Sectional Shape:**

Mesh and composition

**Hole Diameter:**

Between 0.170 inches and 0.190 inches

**Overall Length:**

Between 7.720 inches and 7.780 inches

**Overall Width:**

Between 3.590 inches and 3.650 inches

**Minor Width:**

Between 0.078 inches and 0.093 inches

**Outside Corner Radius:**

Between 0.470 inches and 0.530 inches

**Aperture Width:**

Between 2.350 inches and 2.410 inches

**Aperture Length:**

Between 6.470 inches and 6.530 inches

**Center To Center Distance Between Bolt Holes Along Width:**

Between 1.516 inches and 1.536 inches

**Center To Center Distance Between Bolt Holes Along Length:**

Between 1.427 inches and 1.447 inches

**Outside Edge To Bolt Hole Center Distance Along Width:**

Between 0.334 inches and 0.354 inches

**Outside Edge To Bolt Hole Center Distance Along Length:**

Between 0.316 inches and 0.336 inches

**Cross-sectional Height:**

Between 0.125 inches and 0.140 inches

**Minor Height:**

Between 0.083 inches and 0.103 inches

**Bolt Hole Quantity:**

14

**Environmental Protection Material Location:**

Throughout rf shielding gasket

**Material:**

Steel comp 1010 emi/rfi conductor

**Material Specification:**

Qq-w-461 federal specification single material response emi/rfi conductor

**Surface Treatment:**

Copper emi/rfi conductor and tin emi/rfi conductor

**Surface Treatment Specification:**

Astm-b-227 national specification 1st treatment response emi/rfi conductor and astm-b-33 national specification 2nd treatment response emi/rfi conductor

**Style Designator:**

Non-circular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A032a0

**Mil-std (military Standard):**

Mil-r-3065 spec.