

View Online at <https://aerobasegroup.com/nsn/5999-01-336-7598>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.146 inches and 0.166 inches

Overall Length:

Between 1.173 inches and 1.203 inches

Temperature Rating:

-65.0 degrees celsius and 160.0 degrees celsius

Overall Width:

Between 1.173 inches and 1.203 inches

Aperture Diameter:

Between 0.875 inches and 0.895 inches

Outside Corner Radius:

0.1994 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 0.896 inches and 0.916 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 0.896 inches and 0.916 inches

Outside Edge To Bolt Hole Center Distance Along Width:

0.141 inches

Outside Edge To Bolt Hole Center Distance Along Length:

0.141 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Special Features:

Resistant to solvents and jet fuel

Material:

Silver emi/rfi conductor

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0