

View Online at <https://aerobasegroup.com/nsn/5999-01-337-6384>

Cross Sectional Shape:

Emi

Hole Diameter:

Between 0.209 inches and 0.229 inches

Overall Length:

Between 2.350 inches and 2.650 inches

Tempurature Rating:

-45.0 degrees celsius and 125.0 degrees celsius

Overall Width:

Between 2.350 inches and 2.650 inches

Aperture Diameter:

Between 2.250 inches and 2.450 inches

Outside Corner Radius:

0.284 inches

Center To Center Distance Between Bolt Holes Along Width:

Between 1.928 inches and 1.948 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 1.928 inches and 1.948 inches

Outside Edge To Bolt Hole Center Distance Along Width:

Between 0.201 inches and 0.361 inches

Outside Edge To Bolt Hole Center Distance Along Length:

Between 0.201 inches and 0.361 inches

Cross-sectional Height:

Between 0.027 inches and 0.037 inches

Bolt Hole Quantity:

4

Environmental Protection Material Location:

Throughout rf shielding gasket

Material:

Copper emi/rfi conductorrubber silicone class q environmental seal

Precious Material And Location:

Emi/rfi conductive particles silver

Precious Material:

Silver

Surface Treatment:

Silver emi/rfi conductor

Style Designator:

Non-circular

Test Data Document:

81349-mil-g-83528 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-g-83528/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A032a0