NSN 5999-01-339-2259



Delay Line - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5999-01-339-2259 **Body Style:** Rectangular Frequency Rating: Not rated **Body Length:** 0.800 inches **Body Width:** 0.325 inches **Individual Section Quantity: Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 14 **Voltage Rating:** 5.500 volts **Material And Location:** Plastic, diallyl phthalate, mil-m-14, type sdg body err-100 err-100 phosphor bronze terminal err-100 err-100 **Surface Treatment And Location:** Tin plated terminal Input Impedance Rating: 100.000 ohms **Output Impedance Rating:** 100.000 ohms Frequency Bandwidth: Not rated **Body Depth:** 0.220 inches **Mounting Facility: Terminal Attenuation In Decibels:** Not rated **Signal Delay Method:** Solid state **Delay Time Variation Method:** Tapped **Section Delay Time:**

Segment Quantity Per Section: 10 single section

95.000 nanoseconds single section and 105.000 nanoseconds single section

NSN 5999-01-339-2259

Delay Line - Page 2 of 2



Segme	ent D	elay	Time	•

9.700 nanoseconds single section all segments and 10.300 nanoseconds single section all segments

Delay Time Variation Per Deg Celsius:

Not rated

Pulse Rise Time Rating:

5.0 nanoseconds

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100