# NSN 5999-01-339-2259

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-339-2259

## **Body Style:**

Rectangular

**Frequency Rating:** 

Not rated

# **Body Length:**

0.800 inches

## **Body Width:**

0.325 inches

# Individual Section Quantity:

1

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Inclosure Type:

# Hermetically sealed

#### Mounting Facility Quantity:

14

# Voltage Rating:

5.500 volts

# Material And Location:

Plastic, diallyl phthalate, mil-m-14, type sdg body err-100 err-100 phosphor bronze terminal err-100 err-100

# Surface Treatment And Location:

Tin plated terminal

## Input Impedance Rating:

100.000 ohms

## **Output Impedance Rating:**

100.000 ohms

#### Frequency Bandwidth:

Not rated

## Body Depth:

0.220 inches

#### Mounting Facility:

Terminal

#### Attenuation In Decibels:

Not rated

## Signal Delay Method:

Solid state

# **Delay Time Variation Method:**

Tapped

## Section Delay Time:

95.000 nanoseconds single section and 105.000 nanoseconds single section

# Segment Quantity Per Section:

10 single section

# NSN 5999-01-339-2259

Delay Line - Page 2 of 2



# Segment Delay Time:

9.700 nanoseconds single section all segments and 10.300 nanoseconds single section all segments

# Delay Time Variation Per Deg Celsius:

Not rated

# Pulse Rise Time Rating:

5.0 nanoseconds

# Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

## Fiig:

A32100