## NSN 5999-01-341-0218

Delay Line - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5999-01-341-0218 **Body Style:** Rectangular **Body Length:** 0.800 inches **Body Width:** 0.500 inches **Individual Section Quantity: Longest Vertical Distance Between Mounting Centers:** 0.300 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Inclosure Type: Encased Mounting Facility Quantity: Voltage Rating:** Between 4.750 volts and 5.250 volts **Material And Location:** Ceramic body **Surface Treatment And Location:** Plastic, epoxy body **Body Depth:** 0.165 inches **Mounting Facility: Terminal Signal Delay Method:** Solid state **Delay Time Variation Method: Tapped Section Delay Time:** 25.000 nanoseconds single section **Segment Quantity Per Section:** 5 single section **Segment Delay Time:** 5.000 nanoseconds single section all segments **Pulse Rise Time Rating:** 

4.0 nanoseconds **Terminal Type And Quantity:** 8 pin **Special Features:** 

Two rows, four pins irreqularly spaced per row

## NSN 5999-01-341-0218

Delay Line - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A32100